PRODUCT OVERVIEW

07-2026

TA // COLOR AND MONO MULTIFUNCTIONAL SYSTEMS

Content

Color Systems

A3 Multifunctional Systems page 3
A4 Multifunctional Systems page 6
A4 Print Systems page 9

Mono Systems

A3 Multifunctional Systems page 10
A4 Multifunctional Systems page 13
A3 Print Systems page 16
A4 Print Systems page 17

A3 Multifunctional Systems

Optional features are marked in grey font.

		P-C2480i MFP	2509ci	3509ci	4009ci
COPY	COPY SPEED	24 A4 / 12 A3 pages/min in colour and b/w	25 A4 / 12 A3 pages/min in colour and b/w	35 A4 / 17 A3 pages/min in colour and b/w	40 A4 / 20 A3 pages/min in colour and b/w
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256	256
	STANDARD PAPER FEED	600 (500 + 100 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)
	OPTIONAL PAPER FEED	1 or 2 x 500 sheets	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible
	PAPER CAPACITY, MAX	1,600 sheets	7,150 sheets	7,150 sheets	7,150 sheets
	PAPER FORMAT	A6R-A3	A6R-SRA3/A3+	A6R–SRA3/A3+	A6R–SRA3/A3+
	ORIGINAL FEEDER	Standard	Option: DP-7140, DP-7150, DP-7160 or DP-7170	Option: DP-7140, DP-7150, DP-7160 or DP-7170	Option: DP-7150, DP-7160 or DP-7170
	DUPLEX	Standard	Standard	Standard	Standard
	SYSTEM MEMORY	1.5 GB (max 3 GB)	4 GB RAM, 64 GB SSD/320 GB or 1 TB HDD	4 GB RAM, 64 GB SSD/320 GB or 1 TB HDD	4 GB RAM, 128 GB SSD/320 GB or 1 TB HDD
	ZOOM	25%-400%	25%-400%	25%–400%	25%–400%
	CABINET	Option: no. 62	Option: no. 81	Option: no. 81	Option: no. 81
PRINT	TYPE	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host (2), NFC, Wi-Fi	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14
	EMULATIONS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 2.0, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 2.0, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 2.0, XPS
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025
SCAN	SCAN TYPE	CIS colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP	TCP/IP
FAX	ORIGINALS	max A3	max A3	max A3	max A3
	MODEM SPEED	33.6 kbps	33.6 kbps	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	100/200	1,000/2,000	1,000/2,000	1,000/2,000

A3 Multifunctional Systems

Optional features are marked in grey font.

		5009ci	6009ci	7009ci
COPY	COPY SPEED	50 A4 / 25 A3 pages/min in colour and b/w	60 A4 / 30 A3 pages/min in colour and b/w	70 A4 / 35 A3 pages/min in colour and b/w
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256
	STANDARD PAPER FEED	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)
	OPTIONAL PAPER FEED	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible
	PAPER CAPACITY, MAX	7,150 sheets	7,650 sheets	7,650 sheets
	PAPER FORMAT	A6R-SRA3/A3+	A6R-SRA3/A3+	A6R-SRA3/A3+
	ORIGINAL FEEDER	Option: DP-7150, DP-7160 or DP-7170	Option: DP-7150, DP-7160 or DP-7170	Option: DP-7150, DP-7160 or DP-7170
	DUPLEX	Standard	Standard	Standard
	SYSTEM MEMORY	4 GB RAM, 128 GB SSD/320 GB HDD or 1 TB HDD	4 GB RAM, 128 GB SSD/320 GB HDD or 1 TB HDD	4 GB RAM, 128 GB SSD/320 GB HDD or 1 TB HDD
	ZOOM	25%–400%	25%–400%	25%–400%
	CABINET	Option: no. 81	Option: no. 81	Option: no. 81
PRINT	TYPE	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14
	EMULATIONS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 2.0, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 2.0, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 2.0, XPS
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025
SCAN	SCAN TYPE	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP
FAX	ORIGINALS	max A3	max A3	max A3
	MODEM SPEED	33.6 kbps	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	1,000/2,000	1,000/2,000	1,000/2,000

A3 Multifunctional Systems

Optional features are marked in grey font.

		7515ci	8515ci	9515ci
COPY	COPY SPEED	70 A4 pages/min, 35 A3 pages/min in colour, 75 A4 pages/min, 37 A3 pages/min in b/w	75 A4 pages/min, 37 A3 pages/min in colour, 85 A4 pages/min, 42 A3 pages/min in b/w	80 A4 pages/min, 40 A3 pages/min in colour, 95 A4 pages/min, 47 A3 pages/min in b/w
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256
	STANDARD PAPER FEED	4,350 (2 x 550 + 2 x 1,500 + 250 sheets)	4,350 (2 x 550 + 2 x 1,500 + 250 sheets)	4,350 (2 x 550 + 2 x 1,500 + 250 sheets)
	OPTIONAL PAPER FEED	3,200 sheets (SRA3) or 3,000 sheets (A4) large capacity cassette	3,200 sheets (SRA3) or 3,000 sheets (A4) large capacity cassette	3,200 sheets (SRA3) or 3,000 sheets (A4) large capacity cassette
	PAPER CAPACITY, MAX	7,550 sheets	7,550 sheets	7,550 sheets
	PAPER FORMAT	A6R–SRA3	A6R–SRA3	A6R–SRA3
	ORIGINAL FEEDER	Standard (dual scanner with straight-path function including ultrasonic sensor)	Standard (dual scanner with straight-path function including ultrasonic sensor)	Standard (dual scanner with straight-path function including ultrasonic sensor)
	DUPLEX	Standard	Standard	Standard
	SYSTEM MEMORY	9 GB RAM, 256 GB SSD/1 TB HDD	9 GB RAM, 256 GB SSD/1 TB HDD	9 GB RAM, 256 GB SSD/1 TB HDD
	ZOOM	25%–400%	25%–400%	25%–400%
	CABINET	--	--	--
PRINT	TYPE	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 3.0, USB 2.0-Host(4), Gigabit-Ethernet (10/100/1000BaseTX), SD-Card-Slot, NFC	USB 3.0, USB 2.0-Host(4), Gigabit-Ethernet (10/100/1000BaseTX), SD-Card-Slot, NFC	USB 3.0, USB 2.0-Host(4), Gigabit-Ethernet (10/100/1000BaseTX), SD-Card-Slot, NFC
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ab OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ab OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ab OS 10.14
	EMULATIONS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, OpenXPS, PDF, PPML, XJDF/XJMF	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, OpenXPS, PDF, PPML, XJDF/XJMF	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, OpenXPS, PDF, PPML, XJDF/XJMF
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025
SCAN	SCAN TYPE	CCD/CIS colour and b/w	CCD/CIS colour and b/w	CCD/CIS colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi (1,200 x 1,200 dpi TWAIN Driver)	200, 300, 400, 600 dpi (1,200 x 1,200 dpi TWAIN Driver)	200, 300, 400, 600 dpi (1,200 x 1,200 dpi TWAIN Driver)
	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP
FAX	ORIGINALS	max A3	max A3	max A3
	MODEM SPEED	33.6 kbps	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	2,000	2,000	2,000

A4 Multifunctional Systems

Optional features are marked in grey font.

		302ci	352ci	402ci	502ci
COPY	COPY SPEED	30 A4 pages/min. in colour and b/w	35 A4 pages/min. in colour and b/w	40 A4 pages/min. in colour and b/w	50 A4 pages/min. in colour and b/w
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256	256
	STANDARD PAPER FEED	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)
	OPTIONAL PAPER FEED	1 x 500 + 2 x 500 or 1 x 2,000 sheets	1 x 500 + 2 x 500 or 1 x 2.000 sheets	1 x 500 + 2 x 500 or 1 x 2.000 sheets	1 x 500 + 2 x 500 or 1 x 2.000 sheets
	PAPER CAPACITY, MAX	3,100 sheets	3,100 sheets	3,100 sheets	3,100 sheets
	PAPER FORMAT	A6R-A4	A6R-A4	A6R-A4	A6R-A4
	ORIGINAL FEEDER	Standard	Option: DP-5100, DP-5120, DP-5130	Option: DP-5100, DP-5120, DP-5130	Option: DP-5100, DP-5120, DP-5130
	DUPLEX	Standard	Standard	Standard	Standard
	SYSTEM MEMORY	1.536 MB RAM (max 3.072 MB RAM)	4 GB RAM, 16 GB SSD/320 GB HDD	4 GB RAM, 8 GB SSD, 320 GB HDD	4 GB RAM, 8 GB SSD, 320 GB HDD
	ZOOM	25%-400%	25%-400%	25%-400%	25%-400%
	CABINET	Option: high Nr. 74, low Nr. 75	Option: high Nr. 74, low Nr. 75	Option: high Nr. 74, low Nr. 75	Option: high Nr. 74, low Nr. 75
PRINT	TYPE	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 2.0 (opt.), 10/100/1000BaseTX, USB host (2)	USB 2.0 (opt.), 10/100/1000BaseTX, USB-Host (3), NFC	USB 2.0 (opt.), 10/100/1000BaseTX, USB-Host (3), NFC	USB 2.0 (opt.), 10/100/1000BaseTX, USB-Host (3), NFC
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14
	EMULATIONS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025
SCAN	SCAN TYPE	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP	TCP/IP
FAX	ORIGINALS	max A4	max A4	max A4	max A4
	MODEM SPEED	33,6 kbps	33,6 kbps	33,6 kbps	33,6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	100/200	1,000/2,000	1,000/2,000	1,000/2,000

A4 Multifunctional Systems

Optional features are marked in grey font.

		P-C2157w MFP	P-C2656w MFP	P-C3563i MFP	P-C3567i MFP
COPY	COPY SPEED	21 A4 pages/min in colour and b/w	26 A4 pages/min in colour and b/w	35 A4 pages/min in colour and b/w	35 A4 pages/min in colour and b/w
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256	256
	STANDARD PAPER FEED	300 (1 x 250 + 50 sheets)	300 (1 x 250 + 50 sheets)	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)
	OPTIONAL PAPER FEED	1 x 250 sheets	1 x 250 sheets	3 x 550 sheets	3 x 550 sheets
	PAPER CAPACITY, MAX	550 sheets	550 sheets	2,000 sheets	2,000 sheets
	PAPER FORMAT	A6R–A4	A6R–A4	A6R–A4	A6R–A4
	ORIGINAL FEEDER	Standard (RDF)	Standard (Duplex Scan)	Standard (dual scan)	Standard (dual scan)
	DUPLEX	Standard	Standard	Standard	Standard
	SYSTEM MEMORY	1 GB RAM (max 1 GB)	1 GB RAM (max 1 GB)	1.5 GB RAM (max 3 GB RAM)/64/256/512 GB SSD	1.5 GB RAM (max 3 GB RAM)/64/256/512 GB SSD
	ZOOM	25%–400%	25%–400%	25%–400%	25%–400%
	CABINET	Option: no. 77	Option: no. 77	Option: high no. 82, low no. 83	Option: high no. 82, low no. 83
PRINT	TYPE	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host, SD slot, Wi-Fi	USB 2.0, 10/100/1000BaseTX, USB host, SD slot, Wi-Fi	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 2.0, 10/100/1000BaseTX, USB host (2)
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14
	EMULATIONS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, Open XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, Open XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025
SCAN	SCAN TYPE	CIS colour and b/w	CIS colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP	TCP/IP
FAX	ORIGINALS	max A4	max A4	--	max A4
	MODEM SPEED	33.6 kbps	33.6 kbps	--	33.6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	--	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	100/200	100/200	--	100/200

A4 Multifunctional Systems

Optional features are marked in grey font.

		P-C4063i MFP	P-C4067i MFP	358ci	458ci
COPY	COPY SPEED	40 A4 pages/min in colour and b/w	40 A4 pages/min in colour and b/w	35 A4 pages/min in colour and b/w	45 A4 pages/min in colour and b/w
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256	256
	STANDARD PAPER FEED	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)	650 (1 x 550 + 100 sheets)
	OPTIONAL PAPER FEED	3 x 550 sheets	3 x 550 sheets	3 x 550 sheets	4 x 550 sheets
	PAPER CAPACITY, MAX	2,000 sheets	2,000 sheets	2,000 sheets	2,850 sheets
	PAPER FORMAT	A6R–A4	A6R–A4	A6R–A4	A6R–A4
	ORIGINAL FEEDER	Standard (dual scan with multi-feed detection)	Standard (dual scan with multi-feed detection)	Standard (dual scan)	Standard (dual scan with multi-feed detection)
	DUPLEX	Standard	Standard	Standard	Standard
	SYSTEM MEMORY	2 GB RAM (max 3 GB RAM)/64/256/512 GB SSD	2 GB RAM (max 3 GB RAM)/64/256/512 GB SSD	2 GB RAM (max 3 GB RAM)/64/256/512 GB SSD	2 GB RAM (max 3 GB RAM)/64/256/512 GB SSD
	ZOOM	25%–400%	25%–400%	25%–400%	25%–400%
	CABINET	Option: high no. 82, low no. 83	Option: high no. 82, low no. 83	Option: high no. 82, low no. 83	Option: high no. 82, low no. 83
PRINT	TYPE	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 2.0, 10/100/1000BaseTX, USB host (2)
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14
	EMULATIONS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025
SCAN	SCAN TYPE	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP	TCP/IP
FAX	ORIGINALS	--	max A4	max A4	max A4
	MODEM SPEED	--	33.6 kbps	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	--	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	--	100/200	100/200	100/200

A4 Print Systems

	P-C2651DW	P-C3563DN	P-C4063DN	P458ci
PRINT FORMAT	A6R–A4	A6R–A4	A6R–A4	A6R–A4
PRINT SPEED	26 A4 pages/min in colour and b/w	35 A4 pages/min in colour and b/w	40 A4 pages/min in colour and b/w	45 A4 pages/min in colour and b/w
PRINT RESOLUTION	600 x 600 dpi, 9,600 x 600 dpi level, 1,200 x 1,200 dpi (reduced speed)	600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed)	600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed)	600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed)
STANDARD PAPER FEED	300 (1 x 250 + 50 sheets)	650 (1 x 550 + 100 sheets)	650 (1 x 550 + 100 sheets)	650 (1 x 550 + 100 sheets)
OPTIONAL PAPER FEED	1 x 250 sheets	3 x 550 sheets	3 x 550 sheets	4 x 550 sheets
DUPLEX	Standard	Standard	Standard	Standard
PROCESSOR	Cortex-A9 / 800 MHz	ARM Cortex-A9 dual core/1.2 GHz	ARM Cortex-A9 dual core/1.2 GHz	ARM Cortex-A9 dual core/1.2 GHz
PRINT MEMORY	1 GB RAM (max 1 GB RAM)	1 GB RAM (max 1 GB RAM)	1 GB RAM (max 3 GB RAM)	1 GB RAM (max 3 GB RAM)
INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host, SD slot, Wi-Fi	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 2.0, 10/100/1000BaseTX, USB host (2)
NETWORK CARD OPTIONAL	--	IB-50 Gigabit Ethernet, IB-37/IB-51 WLAN card	IB-50 Gigabit Ethernet, IB-37/IB-51 WLAN card	IB-50 Gigabit Ethernet, IB-37/IB-51 WLAN card
EMULATIONS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, Open XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS

A3 Multifunctional Systems

Optional features are marked in grey font.

		P-3241i MFP	3263i	4063i
COPY	COPY SPEED	32 A4 / 17 A3 pages/min	32 A4 / 17 A3 pages/min	40 A4 / 21 A3 pages/min
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256
	STANDARD PAPER FEED	600 (1 x 500 + 100 sheets)	1,100 (2 x 500 + 100 sheets)	1,100 (2 x 500 + 100 sheets)
	OPTIONAL PAPER FEED	1 or 2 x 500 sheets	2 x 500 sheets or 2 x 1,500 sheets	2 x 500 sheets or 2 x 1,500 sheets
	PAPER CAPACITY, MAX	1,600 sheets	4,100 sheets	4,100 sheets
	PAPER FORMAT	A6R–A3	A6R-A3	A6R-A3
	ORIGINAL FEEDER	Standard	Option: DP-7140, DP-7150, DP-7160 or DP-7170	Option: DP-7140, DP-7150, DP-7160 or DP-7170
	DUPLEX	Standard	Standard	Standard
	SYSTEM MEMORY	2 GB RAM (max 2 GB RAM)	4 GB RAM, 32 GB SSD / 320 GB or 1 TB HDD	4 GB RAM, 32 GB SSD/320 GB or 1 TB HDD
	ZOOM	25%–400%	25%-400%	25%-400%
	CABINET	Option: no. 62	Option: no. 70	Option: no. 70
PRINT	TYPE	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host (2), NFC, Wi-Fi	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB-host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB-host, NFC
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14
	EMULATIONS	PCL6 (PCL 5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, PDF 1.7, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, XPS
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025
SCAN	SCAN TYPE	CIS colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi, 1,200 dpi x 1,200 dpi (only with TWAIN Driver, WIA Driver)	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP
FAX	ORIGINALS	max A3	max A3	max A3
	MODEM SPEED	33.6 kbps	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	300	1,000/2,000	1,000/2,000

A3 Multifunctional Systems

Optional features are marked in grey font.

		5059i	6059i	7059i
COPY	COPY SPEED	50 A4 / 25 A3 pages/min	60 A4 / 30 A3 pages/min	70 A4 / 35 A3 pages/min
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256
	STANDARD PAPER FEED	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)
	OPTIONAL PAPER FEED	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible
	PAPER CAPACITY, MAX	7,150 sheets	7,650 sheets	7,650 sheets
	PAPER FORMAT	A6R-SRA3/A3+	A6R-SRA3/A3+	A6R-SRA3/A3+
	ORIGINAL FEEDER	Option: DP-7150, DP-7160 or DP-7170	Option: DP-7150, DP-7160 or DP-7170	Option: DP-7150, DP-7160 or DP-7170
	DUPLEX	Standard	Standard	Standard
	SYSTEM MEMORY	4 GB RAM, 128 GB SSD/320 GB HDD or 1 TB	4 GB RAM, 128 GB SSD/320 GB HDD or 1 TB	4 GB RAM, 128 GB SSD/320 GB HDD or 1 TB
	ZOOM	25%–400%	25%–400%	25%–400%
	CABINET	Option: no. 81	Option: no. 81	Option: no. 81
PRINT	TYPE	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14
	EMULATIONS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, PDF 2.0, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, PDF 2.0, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, PDF 2.0, XPS
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025
SCAN	SCAN TYPE	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP
FAX	ORIGINALS	max A3	max A3	max A3
	MODEM SPEED	33.6 kbps	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	1,000/2,000	1,000/2,000	1,000/2,000

A3 Multifunctional Systems

Optional features are marked in grey font.

		7565i	8565i	9565i	10565i
COPY	COPY SPEED	75 A4 / 37 A3 pages/min	85 A4 / 42 A3 pages/min	95 A4/ 47 A3 pages/min	105 A4/ 52 A3 pages/min
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256	256
	STANDARD PAPER FEED	4,350 (2 x 550 + 2 x 1.500 + 250 sheets)	4,350 (2 x 550 + 2 x 1.500 + 250 sheets)	4,350 (2 x 550 + 2 x 1.500 + 250 sheets)	4,350 (2 x 550 + 2 x 1.500 + 250 sheets)
	OPTIONAL PAPER FEED	3,200 sheets (SRA3) or 3,000 sheets (A4) large capacity cassette	3,200 sheets (SRA3) or 3,000 sheets (A4) large capacity cassette	3,200 sheets (SRA3) or 3,000 sheets (A4) large capacity cassette	3,200 sheets (SRA3) or 3,000 sheets (A4) large capacity cassette
	PAPER CAPACITY, MAX	7,550 sheets	7,550 sheets	7,550 sheets	7,550 sheets
	PAPER FORMAT	A6R–SRA3	A6R–SRA3	A6R–SRA3	A6R–SRA3
	ORIGINAL FEEDER	Standard (dual scanner with straight-path function including ultrasonic sensor)	Standard (dual scanner with straight-path function including ultrasonic sensor)	Standard (dual scanner with straight-path function including ultrasonic sensor)	Standard (dual scanner with straight-path function including ultrasonic sensor)
	DUPLEX	Standard	Standard	Standard	Standard
	SYSTEM MEMORY	7 GB RAM, 256 GB SSD/1 TB HDD	7 GB RAM, 256 GB SSD/1 TB HDD	7 GB RAM, 256 GB SSD/1 TB HDD	7 GB RAM, 256 GB SSD/1 TB HDD
	ZOOM	25%–400%	25%–400%	25%–400%	25%–400%
	CABINET	--	--	--	--
PRINT	TYPE	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 3.0, USB 2.0-Host(4), Gigabit-Ethernet (10/100/1000BaseTX), SD-Card-Slot, NFC	USB 3.0, USB 2.0-Host(4), Gigabit-Ethernet (10/100/1000BaseTX), SD-Card-Slot, NFC	USB 3.0, USB 2.0-Host(4), Gigabit-Ethernet (10/100/1000BaseTX), SD-Card-Slot, NFC	USB 3.0, USB 2.0-Host(4), Gigabit-Ethernet (10/100/1000BaseTX), SD-Card-Slot, NFC
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14
	EMULATIONS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, OpenXPS, PDF, PPML, XJDF/XJMF	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, OpenXPS, PDF, PPML, XJDF/XJMF	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, OpenXPS, PDF, PPML, XJDF/XJMF	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, OpenXPS, PDF, PPML, XJDF/XJMF
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025
SCAN	SCAN TYPE	CCD/CIS colour and b/w	CCD/CIS colour and b/w	CCD/CIS colour and b/w	CCD/CIS colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi, (1,200 x 1,200 dpi TWAIN Driver)	200, 300, 400, 600 dpi, (1,200 x 1,200 dpi TWAIN Driver)	200, 300, 400, 600 dpi, (1,200 x 1,200 dpi TWAIN Driver)	200, 300, 400, 600 dpi, (1,200 x 1,200 dpi TWAIN Driver)
	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP	TCP/IP
FAX	ORIGINALS	max A3	max A3	max A3	max A3
	MODEM SPEED	33.6 kbps	33.6 kbps	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	2,000	2,000	2,000	2,000

A4 Multifunctional Systems

		P-4021 MFP	P-4026w MFP	P-4027iw MFP
COPY	COPY SPEED	40 A4 pages/min	40 A4 pages/min	40 A4 pages/min
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256
	STANDARD PAPER FEED	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)
	OPTIONAL PAPER FEED	2 x 250 sheets	2 x 250 sheets	2 x 250 sheets
	PAPER CAPACITY, MAX	850 sheets	850 sheets	850 sheets
	PAPER FORMAT	A6R–A4	A6R–A4	A6R–A4
	ORIGINAL FEEDER	Standard (Duplex Scan)	Standard (Duplex Scan)	Standard (Duplex Scan)
	DUPLEX	Standard	Standard	Standard
	SYSTEM MEMORY	1 GB RAM (max 1 GB RAM)	1 GB RAM (max 1 GB RAM)	2 GB RAM (max 2 GB RAM)
	ZOOM	25%–400%	25%–400%	25%–400%
	CABINET	Option: no. 78	Option: no. 78	Option: no. 78
PRINT	TYPE	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	10/100/1000BaseTX, USB 2.0, USB host, SD slot	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14
	EMULATIONS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025
SCAN	SCAN TYPE	CIS colour and b/w	CIS colour and b/w	CIS colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP
FAX	ORIGINALS	--	max A4	max A4
	MODEM SPEED	--	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	--	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	--	100/200	100/200

A4 Multifunctional Systems

Optional features are marked in grey font.

		P-4532 MFP	P-4539 MFP	P-4532i MFP	P-4539i MFP
COPY	COPY SPEED	45 A4 pages/min	45 A4 pages/min	45 A4 pages/min	45 A4 pages/min
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256	256
	STANDARD PAPER FEED	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)
	OPTIONAL PAPER FEED	4 x 500 sheets	4 x 500 sheets	4 x 500 sheets	4 x 500 sheets
	PAPER CAPACITY, MAX	2,600 sheets	2,600 sheets	2,600 sheets	2,600 sheets
	PAPER FORMAT	A6R–A4	A6R–A4	A6R–A4	A6R–A4
	ORIGINAL FEEDER	Standard	Standard	Standard	Standard
	DUPLEX	Standard	Standard	Standard	Standard
	SYSTEM MEMORY	1 GB RAM (max 3 GB RAM), 64/256/512 GB SSD	1 GB RAM (max 3 GB RAM), 64/256/512 GB SSD	1.5 GB RAM (max 3.5 GB RAM), 64/256/512 GB SSD	1.5 GB RAM (max 3.5 GB RAM), 64/256/512 GB SSD
	ZOOM	25%–400%	25%–400%	25%–400%	25%–400%
	CABINET	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80
PRINT	TYPE	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14
	EMULATIONS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025
SCAN	SCAN TYPE	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP	TCP/IP
FAX	ORIGINALS	--	max A4	--	max A4
	MODEM SPEED	--	33.6 kbps	--	33.6 kbps
	COMPRESSION METHOD	--	JBIG, MMR, MR, MH	--	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	--	22/100	--	100/200

A4 Multifunctional Systems

Optional features are marked in grey font.

		P-5539i MFP	P-6039i MFP
COPY	COPY SPEED	55 A4 pages/min	60 A4 pages/min
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256
	STANDARD PAPER FEED	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)
	OPTIONAL PAPER FEED	4 x 500 sheets	4 x 500 sheets
	PAPER CAPACITY, MAX	2,600 sheets	2,600 sheets
	PAPER FORMAT	A6R–A4	A6R–A4
	ORIGINAL FEEDER	Standard (Duplex Scan)	Standard (dual scan with multi-feed detection)
	DUPLEX	Standard	Standard
	SYSTEM MEMORY	1.5 GB RAM (max 3.5 GB RAM), 64/256/512 GB SSD	1.5 GB RAM (max 3.5 GB RAM), 64/256/512 GB SSD
	ZOOM	25%–400%	25%–400%
	CABINET	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80
PRINT	TYPE	Integrated within the system	Integrated within the system
	INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host, SD slot
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ex OS 10.14
	EMULATIONS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025
SCAN	SCAN TYPE	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	NETWORK PROTOCOLS	TCP/IP	TCP/IP
FAX	ORIGINALS	max A4	max A4
	MODEM SPEED	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	100/200	100/200

A3 Print Systems

	P-6040DN
PRINT FORMAT	A6R–SRA3
PRINT SPEED	60 A4 / 30 A3 pages/min
PRINT RESOLUTION	1,200 x 1,200 dpi
STANDARD PAPER FEED	1,150 (2 x 500 + 150 sheets)
OPTIONAL PAPER FEED	2 x 500, 2 x 1,500, 3,000 sheets
DUPLEX	Standard
PROCESSOR	Freescale QorIQ T1024 (Dual Core) 1.2 GHz
PRINT MEMORY	4 GB RAM, 8 GB SSD, 320 GB HDD
INTERFACES	USB 2.0, USB host, 10/100/1000BaseTX, NFC
INTERFACES OPTIONAL	--
EMULATIONS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PDF 1.7, PRESCRIBE lle, XPS

A4 Print Systems

	P-3523DW	P-4021DN	P-4021DW
PRINT FORMAT	A6R–A4	A6R–A4	A6R–A4
PRINT SPEED	35 A4 pages/min	40 A4 pages/min	40 A4 pages/min
PRINT RESOLUTION	600 x 600 dpi, 1,200 x 1,200 dpi	600 x 600 dpi, 1,200 x 1,200 dpi	600 x 600 dpi, 1,200 x 1,200 dpi
STANDARD PAPER FEED	350 (250 + 100 sheets)	350 (250 + 100 sheets)	350 (250 + 100 sheets)
OPTIONAL PAPER FEED	2 x 250 sheets	2 x 250 sheets	2 x 250 sheets
DUPLEX	Standard	Standard	Standard
PROCESSOR	ARM Cortex A53 single 1,0 GHz + ARM Cortex-M3 100 MHz	Cortex-A9 / 800 MHz	Cortex-A9 / 800 MHz
PRINT MEMORY	512 MB RAM (max 512 MB RAM)	512 MB RAM (max 512 MB RAM)	512 MB RAM (max 512 MB RAM)
INTERFACES	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi	10/100/1000BaseTX, USB 2.0, USB host, SD slot	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi
INTERFACES OPTIONAL	--	--	--
EMULATIONS	PCL6 (PCL 5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, PDF 2.0, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS

	P-4534DN	P-5034DN	P-5534DN	P-6034DN
PRINT FORMAT	A6R–A4	A6R–A4	A6R–A4	A6R–A4
PRINT SPEED	45 A4 pages/min	50 A4 pages/min	55 A4 pages/min	60 A4 pages/min
PRINT RESOLUTION	1,200 x 1,200 dpi	1,200 x 1,200 dpi	1,200 x 1,200 dpi	1,200 x 1,200 dpi
STANDARD PAPER FEED	600 (500 + 100 sheets)	600 (500 + 100 sheets)	600 (500 + 100 sheets)	600 (500 + 100 sheets)
OPTIONAL PAPER FEED	4 x 500 sheets	4 x 500 sheets	4 x 500 sheets	4 x 500 sheets
DUPLEX	Standard	Standard	Standard	Standard
PROCESSOR	ARM Cortex-A53 Dual Core, 1,4 GHz	ARM Cortex-A53 Dual Core, 1,4 GHz	ARM Cortex-A53 Dual Core, 1,4 GHz	ARM Cortex-A53 Dual Core, 1,4 GHz
PRINT MEMORY	512 MB (max 2.5 GB)	512 MB (max 2.5 GB)	512 MB (max 2.5 GB)	512 MB (max 2.5 GB)
INTERFACES	10/100/1000BaseTX, USB 2.0, USB host (2), SD slot	10/100/1000BaseTX, USB 2.0, USB host (2), SD slot	10/100/1000BaseTX, USB 2.0, USB host (2), SD slot	10/100/1000BaseTX, USB 2.0, USB host (2), SD slot
INTERFACES OPTIONAL	IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card	IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card	IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card	IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card
EMULATIONS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS

triumph-adler.com

TA Triumph-Adler

We develop **individual processes in the fields of document solutions, information and IT.** Document technology is our core business and we continuously develop our portfolio. At the same time, we assist our customers in creating flexible and modern workplaces with our pioneering mobile solutions and cloud services. Efficient processes are crucial for the success of a company. **We can assist you with solutions for saving time and money with your workflows** and support you with our expertise in implementing professional hardware and software solutions.

TA Triumph-Adler
The Document Business
A KYOCERA GROUP COMPANY

07/2026