

Technical data: 7515ci • 8515ci • 9515ci

GENERAL

Type	Console Unit
Function	Copy, print, scan, optional: fax
Print technology	Laser colour and b/w
Original format	max A3 from platen glass
Original feeder	Dual scanner with straight-path function for special media, including ultrasonic sensor for multi-feed detection + staple detection sensor (A6R-A3, capacity: 500 sheet A4 (80g/m ²), banners up to 2,200mm, paper weight 35-220 g/m ² [simplex], 50-220 g/m ² [duplex]) Straight-path function: 50 sheet (80g/m ²) paper weight (35-500 g/m ²), custom formats from 53,98mm - 297mm (width) and 85.6mm - 432mm (length)
Copy/print speed	7515ci: max 70 A4 pages/min and max 35 A3 pages/min in colour and max 75 A4 pages/min and max 37 A3 pages/min in b/w, 8515ci: max 75 A4 pages/min and max 37 A3 pages/min in colour and max 85 A4 pages/min and max 42 A3 pages/min in b/w 9515ci: max 80 A4 pages/min and max 40 A3 pages/min in colour and max 95 A4 pages/min and max 47 A3 pages/min in b/w
1st page (Copy/Print)	7515ci: Colour: 5.5/5.0 seconds ¹ , b/w: 4.1/3.7 seconds ¹ 8515ci: Colour: 5.5/5.0 seconds ¹ , b/w: 4.1/3.7 seconds ¹ 9515ci: Colour: 5.5/5.0 seconds ¹ , b/w: 4.1/3.7 seconds ¹
Warm-up time	45 seconds ¹ (7515ci) 60 seconds ¹ (8515ci/9515ci)
Copy resolution	600 x 600 dpi
Greyscales	256
Paper feed	1 x 550 sheet universal cassettes (A6R-SRA3 [max 330.2 x 457 mm]), 1 x 550 sheet universal cassettes (A6R-SRA3 [max 330.2 x 487 mm]), 2 x 1,500 sheet large capacity cassette (A4), 250 sheet multi-bypass (A6R-SRA3, Banner [330.2 x 1,219 mm])
Paper weights	Universal cassette 52-300 g/m ² , large capacity cassette 52-300 g/m ² , multi-bypass 52-300 g/m ² , duplex 52-256 g/m ²
Paper output	250 sheet A4 (upper tray) and 100 sheet A4 (lower tray) with Copy tray type D ³ , 70 sheet A4 (right tray)
System memory	9 GB RAM, 256 GB SSD ¹
Continuous copying	1-9,999 copies
Zoom	25 %-400 % in steps of 1 %
Functions	Adjustable colour touch screen (10.1 inch), duplex, 1,000 management codes, skip blank pages, motion sensor, encryption/overwriting of hard disk data (Data Security Kit), trusted platform module (TPM), secure boot und runtime integrity check, simple certificate enrollment protocol (SCEP), TLS 1.3, OCSP, CRL, S/MIME, SIEM-Support, Allowlisting, fax server connectivity etc

DIMENSIONS/WEIGHT

Dimensions	Standard: 1,227 x 685 x 660 mm (H x W x D) With Copy Tray Typ D ² : 1,227 x 1,019 x 660 mm (H x W x D)
Weight	approx. 165 kg
ENVIRONMENT	
Mains voltage	2022/2025
Power consumption	approx. 2,400 W max, approx. 1,200/1,320/1,260 W in operation (7515ci/8515ci/9515ci), approx. 130 W in stand-by mode, approx. 0.5 W in sleep mode, TEC value: 1.45/1.62/1.79 kWh/week (7515ci/8515ci/9515ci)
Noise level	7515ci/8515ci/9515ci: approx. 54.7/54.9/55.1 dB(A) in operation colour mode, 55.7/55.6/55.8 dB(A) in operation mono mode, standby mode: 37.8/37.8/45.2 dB(A) (ISO 7779/9296)
Safety	GS/TÜV, CE

PRINT SYSTEM

Type	Integrated within the system
Print format	A6R-SRA3
Print resolution	max 2,400 x 2,400 dpi
Processor	QorIQ LS1046A (Quad Core) 1.6 GHz
Interfaces	USB 3.0, USB 2.0-Host(4), Gigabit-Ethernet (10/100/1000BaseTX), SD-Card-Slot, NFC
Page description language	PRESCRIBE
Operating systems	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022/2025, Linux, Chrome OS, Mac ab OS 10.14
Emulations	PCL6 (Sc, XL), KPDL 3 (PostScript 3 compatible), XPS, OpenXPS, PDF, PPML, XJDF/XJMF
Functions	USB direct printing, PDF/XPS direct printing, super resolution imaging (only KX driver), SNMPv3, printing of e-mails, private printing, EcoPrint, barcode printing, Mobile Print (Android/iOS)/Apple AirPrint, NFC, Wi-Fi Direct ³

SCAN SYSTEM

Scan type	CCD and CIS colour and b/w
Scan format	max A3
Scan speed	max 150/300 (simplex/duplex) A4 originals/min in colour and b/w (300 dpi)
Scan resolution	200 dpi, 300 dpi, 400 dpi, 600 dpi, (1,200 x 1,200 dpi TWAIN Driver)
Scan mode	Photo, text, photo/text, OCR
File types	TIFF, PDF, PDF/A, high compression PDF, encrypted PDF, JPEG, XPS, Open XPS, Microsoft office formats
Interfaces	10/100/1000BaseTX
Network protocol	TCP/IP
Operating systems	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022

Functions	Scan to SMB, scan to e-mail, scan to FTP, scan to USB, TWAIN scan, WIA scan, SMTP authentication, LDAP, multi crop scan, handwriting enhancement, document guard, cloud capture functionality, image defect prevention, ID-scan, OCR text recognition
------------------	---

OPTIONAL FAX SYSTEM 14

Compatibility	Super G3
Original format	max A3
Modem speed	33.6 kbps
Transmission speed	3 seconds or less using JBIG
Compression method	JBIG, MMR, MR, MH
Fax resolution	Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi), 600 x 600 dpi
Fax memory	170 MB
Abbreviated dial	2,000 numbers
One touch dial	1,000 numbers
Group dial	500 numbers
Operating systems	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022
Functions	Network fax driver, automatic redialling, delayed transmission, max 2 fax kits for parallel transmission and reception

OPTIONS

Finisher	DF-7200 (capacity: 4,000 sheet A4, stapling max 65 sheet A4), DF-7210 (capacity: 4,000 sheet A4, stapling max 100 sheet A4), PH-7220 hole punch unit for DF-7200 and DF-7210, BF-7200 brochure module for DF-7200/DF-7210 (max 20 sheet saddle stitching and folding A4/SRA3, tri-folding max 5 sheet A4), MT-7200 (B) Multi tray for DF-7200/DF-7210, IS-7200 Inserter (compatible with DF-7200/DF-7210), ZF-7200 Z-fold unit (compatible with DF-7200/DF-7210)
Paper feed	PF-7210 (3,200 sheet large capacity tray [A6R-SRA3], side deck), PF-7200 (3,000 sheet large capacity tray [A4], side deck)
Professional colour management	Fiery® Controller (Printing System 18 depends on Printing System Interface Kit 18)
Other options	Internet fax kit (A), Card authentication kit(B), Keyboard holder 10, Banner guide 12, UG-33 ThinPrint® kit, UG-34 Emulation option kit, IB-53 Gigabit Ethernet card, IB-54 WLAN card (2.4/5 GHz IEEE802.11/b/g/n, Wi-Fi direct, WPA3), IB-55 WLAN card (2.4GHz, IEEE802.11/b/g/n, Wi-Fi direct, WPA3), IB-37 WLAN card (2.4/5 GHz, IEEE802.11a/b/g/n/ac, Wi-Fi direct) or IB-38 WLAN card (2.4 GHz IEEE 802.11 b/g/n Wi-Fi direct), Copy Tray Typ D, DT-730 (B) Document tray, NK-7120(B) Numeric Keyboard (10 keys), HD-16 (1 TB HDD)

¹ Depending on operating status
² For copy, print, scan, fax
³ optional
⁴ IB-38/IB-55 is only available for selected countries outside the EU



Specifications subject to change without notice.
Image shows machine with optional accessories.

TA Triumph-Adler is the document business expert. We offer our clients individual analysis, consultancy and efficient document workflows – not only on paper, but also electronically and with long-term service. For whenever professional users manage, print, photocopy, fax, present or archive documents, or need to optimise processes, TA Triumph-Adler concepts and solutions are the first choice. Our customers benefit greatly from the user-optimised technologies offered by our innovative systems. TA Triumph-Adler and the TA Triumph-Adler logo are registered trademarks of TA Triumph-Adler GmbH. All other brand names are the registered trademarks of their respective owners.

TA Triumph-Adler