

Technical Data:

P-3523DW • P-4021DN • P-4021DW

GENERAL		DIMENSIONS/WEIGHT		OPTIONS	
Type	Desktop	Dimensions (H x W x D)	272 x 375 x 393 mm	Paper feed	max 2x PF-1100 (250 sheet universal cassette [A6-A4, 60-163 g/m ²])
Function	Print	Weight	approx. 14 kg	Other options	Card authentication kit (B), UG-33 ThinPrint® kit, UG-50 Trusted Platform Module, cabinet no. 78
Print technology	Laser b/w	ENVIRONMENT			
Print speed	P-3523DW: max 35 A4 pages/min, duplex: max 18 pages/min P-4021DN/P-4021DW: max 40 A4 pages/min, duplex: max 20 A4 pages/min	Mains voltage	220/240 V, 50(60 Hz)		
1st page¹	6.4 sec	Power consumption	P-3523DW: approx. 1,085 W max, approx. 481 W in operation, approx. 6 W in stand-by mode, approx. 0.3 W in sleep mode, TEC value: 0.3 KWh/week P-4021DN/P-4021DW: approx. 1,085 W max, approx. 556 W in operation, approx. 6 W in stand-by mode, approx. 0.3 W in sleep mode, TEC value: 0.34 KWh/week		
Warm-up time	15 sec ¹	Noise level	approx. 52,1/ 51,6 / 51,6 dB(A) in operation, not measureable in stand-by mode (ISO 7779/9296)		
Greyscales	256	Safety	GS/TÜV, CE		
Paper feed	1 x 250 sheet universal cassette (A6R-A4), 100 sheet multi-bypass (A6R-A4 [min 70 x 148 mm, max 216 x 356 mm])	PRINT SYSTEM			
Paper weights	Universal cassette 60-163 g/m ² , multi-bypass 60-220 g/m ² , duplex 60-163 g/m ²	Type	Integrated within the system		
Paper output	250 sheets A4	Print format	A6R-A4		
System memory	512 MB RAM	Print resolution	600 x 600 dpi, max. 1,200 x 1,200 dpi		
Display	LCD display 128 x 64 dots, half size 21 characters x 5 lines with numeric keypad	Processor	ARM Cortex A53 single 1.0GHz + ARM Cortex-M3 100MHz		
Functions	Duplex, job reservation, job programs, 20 management codes, Secure Boot ³ , Runtime Integrity Check ³ , Simple Certificate Enrollment Protocol (SCEP), TLS 1.3, OCSP, CRL ⁴ , SIEM-Support etc.	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (1), SD-card slot, Wi-Fi ²		
		Network protocols	TCP/IP, Net BEUI		
		Operating systems	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9		
		Emulations	PCL6 (PCL 5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, PDF 2.0, XPS		
		Functions	USB direct printing, PDF/XPS direct printing, printing of e-mails, private printing, quiet mode (half speed mode), barcode printing, Mobile Print (Android/iOS), Apple AirPrint, Universal print, Wi-Fi ²		

- ¹ depending on operating status.
² P-3523DW/P-4021DW
³ UG-50 Trusted Platform Module necessary
⁴ optional SD card required








To enable HyPAS functionality additional memory is required. Specifications subject to change without notice. Image shows machine with optional accessories.

TA Triumph-Adler is the document business expert. We offer our clients individual analysis, consultancy and efficient document workflows – not only on paper, but also electronically and with long-term service. For whenever professional users manage, print, photocopy, fax, present or archive documents, or need to optimise processes, TA Triumph-Adler concepts and solutions are the first choice. Our customers benefit greatly from the user-optimised technologies offered by our innovative systems. TA Triumph-Adler and the TA Triumph-Adler logo are registered trademarks of TA Triumph-Adler GmbH. All other brand names are the registered trademarks of their respective owners.

TA Triumph-Adler