

Safety data sheet DCC 2840

Date: October 1, 2009

UTAX GmbH, Ohechaussee 235, 22848 Norderstedt, Tel.: +49 40 52849-0

Setting-up conditions:

The system should have more than 10 cm distance to the wall and minimum 30 cm distance to the margin, to afford sufficiently circulation of air and so a maintenance can accomplish without any difficulty. The system should not set up in dusty rooms or in rooms while operating with ammonium gas. The atmospheric moisture should amount 15–80%, the room ambient temperature 10–32,5°C.

Safety symbol:

The system bears the CE-mark and TÜV/GS-mark.

It is in accordance with the requirements: EN 60950/60825
 EN 55022/55024/61000

The system bears the TÜV/GS-mark.
 Certificate-No.: S1 50139649



Material:

Toner: see separate safety data sheet
 RoHS: conforms with the RoHS-directive 2002/95/EG
 Drum: a-Si (amorph Silicium)
 Exposure: Xenonlamp
 Paper: The system is adequate for the handling of recycling-paper, with confirms to the EN 12281:2002

Power consumption in Watt:

Heat emission in kj/h:

Maximum:	1,656	5,962
Operation:	1,150	4,140
Stand-by:	210	756
LowPower mode:	130	468
Sleep-mode:	19	68



The system bears the Energy Star.
 TEC Value kW/h: 9.6.

By the complete separation of the system from the net (e.g. adjustable connector strip) a capacity can be prevented.

Substance emission according to Blue Angel Mark:

	Measurement (mg/h)		Limit value (mg/h)	
	b/w	Colour	b/w	Colour
Ozone:	0.1	0.1	1.5	3
Dust:	4	3.3	4	4
Styrene:	not measurability	not measurability	1	1.8
Benzyl:	not measurability	not measurability	< 0.05	< 0.05
TVOC operation:	2.2	2.2	10	18
TVOC stand-by:	0.2	0.2	10	18

Noise emission according to Blue Angel Mark:

Operation b/w: 68 dB(A) L_{WAd}
 Operation colour: 68.2 dB(A) L_{WAd}

Stand-by b/w: 39 dB(A) L_{WA}
 Stand-by colour: 39 dB(A) L_{WA}

Noise emission according to DIN 7779/ISO 9296:

Operation: 65.5 dB(A)

Stand-by: 56.9 dB(A)

L_{WA} (Sound-power level) indicates, like much noise altogether, thus into all directions, is radiated.

L_{WAd} results, deviating from DIN EN ISO 7779:2002, by the combined job scanning and printing.

Miscellaneous information:

The confected declarations on this data sheet become prepared towards best knowledge according our present standard of knowledge. This information's constitute no assurance of any attributes. These information's are not allowed to be collected for other products or become transfused.