

Umweltdatenblatt

2506ci

Sicherheitszertifikate	EN 60950 / 60825 EMC: EN 55022 / 55024 / 61000	
Umweltzertifikate	Blauer Engel (nach RAL-UZ 205), ENERGY STAR 2.0, RoHs	
Leistungsaufnahme / Wärmeabgabe	<u>Leistungsaufnahme</u>	<u>Wärmeabgabe</u>
	Maximal (inkl. Optionen):	1750 W 6300 kJ/h
	Betrieb (Kopieren):	500 W 1800 kJ/h
	Bereit:	40 W 144 kJ/h
	Energiesparmodus:	40 W 144 kJ/h
	Ruhemodus:	0,9 W 3,2 kJ/h
	Ausgeschaltet:	0,3 W 1,1 kJ/h
Typischer Stromverbrauch (TEC)	1,1 kWh/Woche (gem. ENERGY STAR 2.0)	
Aufstellhinweise	Das Multifunktionsgerät sollte so aufgestellt werden, dass sowohl seitlich, als auch vor und hinter dem System ausreichend Platz für die Bedienung und zur Wartung frei gehalten wird. Für eine gute Belüftung sorgen. Das MFP-System nicht in staubigen Räumen aufstellen und vor Ammoniakdämpfen schützen. Bitte beachten Sie die Hinweise im Anwenderhandbuch.	
Luftfeuchtigkeit	10% - 80%	
Raumtemperatur	10,0°C – 32,5°C	
Geräuschemission (gem. ISO 7779)	Surface sound pressure level (Messung in 1m Entfernung, Durchschnitt aus Einzelmessungen)	
	Betrieb:	SW-Modus: 48,5 dB(A) L _{pA} Farbmodus: 48,6 dB(A) L _{pA}
	Bereit:	30,1 dB(A) L _{pA}
	Operator position (Messung in Bedienerposition)	
	Betrieb:	SW-Modus: 50,8 dB(A) L _{pA} Farbmodus: 51,0 dB(A) L _{pA}
	Bereit:	32,1 dB(A) L _{pA}
	Schalleistungspegel entsprechend RAL-UZ 205	
	Betrieb:	SW-Modus: 65,9 dB(A) L _{WAd} Farbmodus: 66,0 dB(A) L _{WAd}
	Bereit:	44,5 dB(A) L _{WA}
Lichtquelle	Belichtung Trommel: Laser	
Emissionen	nach RAL-UZ 205	
	TVOC (Betrieb):	Farbmodus: 6,9 mg/h
	TVOC (Bereit):	Farbmodus: 0,17 mg/h
	Benzol:	Farbmodus: < Nachweisgrenze
	Styrol:	Farbmodus: 0,38 mg/h
	Ozon:	Farbmodus: < Nachweisgrenze
	Staub:	Farbmodus: 0,18 mg/h

Environmental data sheet

2506ci

Safety Approvals	EN 60950 / 60825 EMC: EN 55022 / 55024 / 61000																								
Environmental Certificates	Blue Angel Mark (RAL-UZ 205), ENERGY STAR 2.0, RoHs																								
Power consumption / Heat emission	<table border="0"> <thead> <tr> <th></th> <th><u>Power consumption</u></th> <th><u>Heat emission</u></th> </tr> </thead> <tbody> <tr> <td>Maximum (incl. options):</td> <td>1750 W</td> <td>6300 kJ/h</td> </tr> <tr> <td> Copying:</td> <td>500 W</td> <td>1800 kJ/h</td> </tr> <tr> <td> Ready:</td> <td>40 W</td> <td>144 kJ/h</td> </tr> <tr> <td> Low power mode:</td> <td>40 W</td> <td>144 kJ/h</td> </tr> <tr> <td> Sleep-mode:</td> <td>0.9 W</td> <td>3.2 kJ/h</td> </tr> <tr> <td> Plug-in off-mode:</td> <td>0.3 W</td> <td>1.1 kJ/h</td> </tr> </tbody> </table>		<u>Power consumption</u>	<u>Heat emission</u>	Maximum (incl. options):	1750 W	6300 kJ/h	Copying:	500 W	1800 kJ/h	Ready:	40 W	144 kJ/h	Low power mode:	40 W	144 kJ/h	Sleep-mode:	0.9 W	3.2 kJ/h	Plug-in off-mode:	0.3 W	1.1 kJ/h			
	<u>Power consumption</u>	<u>Heat emission</u>																							
Maximum (incl. options):	1750 W	6300 kJ/h																							
Copying:	500 W	1800 kJ/h																							
Ready:	40 W	144 kJ/h																							
Low power mode:	40 W	144 kJ/h																							
Sleep-mode:	0.9 W	3.2 kJ/h																							
Plug-in off-mode:	0.3 W	1.1 kJ/h																							
TEC (ENERGY STAR 2.0)	1.1 kWh/week																								
Installation Notes	The unit should be placed in a way, that there is adequately space for operation and maintenance on both sides, as well as in front and behind the system. Provide adequate ventilation. Do not set up the unit in dusty rooms, and protect against ammonia vapors. Please follow the instructions in the user manual.																								
Humidity	10% - 80%																								
Room Temperature	10.0°C – 32.5°C																								
Noise Emission (According to ISO 7779)	<p>Surface sound pressure level (measurement in 1 m distance; average of single measurements)</p> <table border="0"> <tr> <td>Operation:</td> <td>BW-Mode: 48.5 dB(A) L_{pA}</td> <td>colour.mode: 48.6 dB(A) L_{pA}</td> </tr> <tr> <td>Ready:</td> <td>30.1 dB(A) L_{pA}</td> <td></td> </tr> <tr> <td colspan="3">Operator position</td> </tr> <tr> <td>Operation:</td> <td>BW-Mode: 50.8 dB(A) L_{pA}</td> <td>colour.mode: 51.0 dB(A) L_{pA}</td> </tr> <tr> <td>Ready:</td> <td>32.1 dB(A) L_{pA}</td> <td></td> </tr> <tr> <td colspan="3">According to RAL-UZ 205</td> </tr> <tr> <td>Operation:</td> <td>BW-Mode: 65.9 dB(A) L_{WAAd}</td> <td>colour.mode: 66.0 dB(A) L_{WAAd}</td> </tr> <tr> <td>Ready:</td> <td>44.5 dB(A) L_{WA}</td> <td></td> </tr> </table>	Operation:	BW-Mode: 48.5 dB(A) L _{pA}	colour.mode: 48.6 dB(A) L _{pA}	Ready:	30.1 dB(A) L _{pA}		Operator position			Operation:	BW-Mode: 50.8 dB(A) L _{pA}	colour.mode: 51.0 dB(A) L _{pA}	Ready:	32.1 dB(A) L _{pA}		According to RAL-UZ 205			Operation:	BW-Mode: 65.9 dB(A) L _{WAAd}	colour.mode: 66.0 dB(A) L _{WAAd}	Ready:	44.5 dB(A) L _{WA}	
Operation:	BW-Mode: 48.5 dB(A) L _{pA}	colour.mode: 48.6 dB(A) L _{pA}																							
Ready:	30.1 dB(A) L _{pA}																								
Operator position																									
Operation:	BW-Mode: 50.8 dB(A) L _{pA}	colour.mode: 51.0 dB(A) L _{pA}																							
Ready:	32.1 dB(A) L _{pA}																								
According to RAL-UZ 205																									
Operation:	BW-Mode: 65.9 dB(A) L _{WAAd}	colour.mode: 66.0 dB(A) L _{WAAd}																							
Ready:	44.5 dB(A) L _{WA}																								
Light Source	Exposure drum: Laser																								
Emissions	<p>According to RAL-UZ 205</p> <table border="0"> <tr> <td>TVOC (Operation):</td> <td>colour-mode: 6.9 mg/h</td> </tr> <tr> <td>TVOC (Ready):</td> <td>colour-mode: 0.17 mg/h</td> </tr> <tr> <td>Benzene:</td> <td>colour-mode: < limit of detection</td> </tr> <tr> <td>Styrene:</td> <td>colour-mode: 0.38 mg/h</td> </tr> <tr> <td>Ozone:</td> <td>colour-mode: < limit of detection</td> </tr> <tr> <td>Dust:</td> <td>colour-mode: 0.18 mg/h</td> </tr> </table>	TVOC (Operation):	colour-mode: 6.9 mg/h	TVOC (Ready):	colour-mode: 0.17 mg/h	Benzene:	colour-mode: < limit of detection	Styrene:	colour-mode: 0.38 mg/h	Ozone:	colour-mode: < limit of detection	Dust:	colour-mode: 0.18 mg/h												
TVOC (Operation):	colour-mode: 6.9 mg/h																								
TVOC (Ready):	colour-mode: 0.17 mg/h																								
Benzene:	colour-mode: < limit of detection																								
Styrene:	colour-mode: 0.38 mg/h																								
Ozone:	colour-mode: < limit of detection																								
Dust:	colour-mode: 0.18 mg/h																								